



Unify Your Network, Simply and Cost Effectively

Imagine a single system that does it all using your existing IP network: from voice to data to video. One that combines the advantages of network-based telephony and the features of traditional PBX systems. All while reducing your infrastructure, lowering capital expenditure and operational costs, and increasing productivity.

With the Strata CIX™ and Strata Net networking, you can take full advantage of today's most advanced communications applications, while receiving these important benefits:

- Save money by avoiding costly long-distance charges on calls between various locations.
- Extend full telephone functionality to remote users via IP telephones connected to your private intranet or the Internet, providing full-featured desk phone capability to all users no matter where they are located.
- Reduce costs by transmitting voice calls via the Internet or your private intranet.
- Provide one integrated system for all your office locations by networking multiple Strata CIX systems to work together as one system.
- Share capabilities enterprise-wide, from centralized attendant services, a single voice mail system, and centralized call center operations, to simplified internal extension dialing, and SMDR.
- Turn a long-distance call into a local call by "hopping off" the network as needed.

Strata Net is a private networking application for inter-connecting Toshiba systems to work as one system.

- Strata Net delivers a rich set of calling features across multiple Strata CIX systems throughout your enterprise.
- Your users benefit from transparent dialing and simple feature operation.
- Advanced networking features include Centralized Voice Mail, Centralized Attendant, Network SMDR, and Station DSS button appearances across all nodes.
- Alternate Routing provides for toll bypass configurations and automatic recovery from network disruptions.

So if you need to interconnect your main office with branch locations and/or remote users, the Strata CIX with Strata Net networking is the solution.

Networking Solutions

SPECIFICATIONS

System Compatibility	Strata CIX100, CIX200, CIX670.
Connection Types	Strata CIX systems are interconnected via ISDN or IP. <ul style="list-style-type: none">• DS1 (T1) circuits provide ISDN-type inter-connectivity.• Strata Net IP provides full Strata Net connectivity and capabilities over an IP network (VPN WAN, Internet, intranet, frame relay, fiber, or wireless).
Maximum Nodes	Up to 128 nodes can be accommodated within the Strata Net numbering plan. Up to four nodes connected in tandem can give satisfactory performance with regard to latency. As with any network design, transport delay, speech volume and other issues must be carefully considered.
Coordinated Numbering	Users can call each other across network nodes with simple network directory numbers. This eliminates the user's need for access codes and network maps. Calls that encounter a busy or unanswered destination can be forwarded to any node in the network, including a centralized voice mail system or attendant.
Alternative Routing	Each Strata CIX can be programmed for thousands of routing patterns for Strata Net alone. This allows the creation of networks in which calls can be automatically re-routed around network disruptions. Centralized facilities and features can continue to work and users will be unaware of problems while they are being repaired. Alternate Routing also permits Toll Bypass in which Strata Net can be used to deliver a public call from a point in the network where toll charges are minimized. Such a scheme is known as "Hop Off" for the ability of the private network to determine the point at which the call will hop off to the public network.
Centralized Attendant	One attendant can serve an entire Strata Net. Station users only need to dial "0" to reach the centralized attendant regardless of the node in which they reside. The attendant can reach any station in the network using its Network Directory Number. Trunks attached to any network node can be programmed to terminate to the centralized attendant and their source and calling party information will be delivered to the attendant's display. The BLF appearances of stations from remote nodes can appear on the centralized Attendant Console.
Centralized Voice Mail	A Toshiba Stratagy™ voice mail system attached to any Strata Net network node can serve users throughout the enterprise. Unanswered calls will be forwarded to the voice mail, the source and calling conditions identified and the appropriate voice mailbox greeting will be played. The voice mail system can control message waiting indications throughout the network as messages are left and retrieved. A single network can even support multiple centralized voice mail systems with each station being programmed for the appropriate system. Record to voice mail and voice mail soft keys are available across all network nodes from a single Stratagy voice mail system.
Network SMDR	An external Strata Net call will generate a call record at the terminating node for that call. Transit nodes will not generate records. The records can be stored in customer-supplied external buffers at each node. Polling call accounting software can gather and organize the data from multiple nodes. Local buffering provides survivability in the event of network disruption.
Network DSS/BLF	Telephone DSS buttons can appear across the Strata Net network. This enables a user's DSS button to function in all nodes in a CIX network. The DSS function works within or across a network.

Toshiba America Information Systems, Inc., Digital Solutions Division

9740 Irvine Blvd., Irvine, CA 92618-1697 (949) 583-3700 www.telecom.toshiba.com

© 2005 Toshiba America Information Systems, Inc., Digital Solutions Division. Printed in U.S.A. Strata is a registered trademark of Toshiba Corporation. Stratagy is a registered trademark of Toshiba America Information Systems, Inc. Specifications subject to change without notice. Some features require optional hardware/software to support full capabilities.

Literature Order #: DSD-CIX-BR-Netw-DS-VA/4500049